

## ViewStation Group Conferencing Products

System Type	Product Placement	Differentiating Features	Max Data Rate H.320	Max Data Rate H.323	Network Interface	Options Available	Monitor Support	Multipoint Capability
<b>ViewStation SP128</b>	Small room system 1-3 people	Document camera or VCR playback Microphone head set (optional) 1 LAN port Includes 1 mic pod	128 Kbps	768 Kbps	ISDN, Ethernet/LAN	N/A	1	N/A
<b>ViewStation SP384</b>	Small room system 1-3 people	Document camera or VCR playback Microphone head set (optional) 1 LAN port Includes 1 mic pod	384 Kbps	768 Kbps	ISDN, Ethernet/LAN	N/A	1	N/A
<b>ViewStation 128</b>	Medium or large room system 1-10 people	Document camera & VCR playback 2nd mic pod (optional) 2-port LAN hub * Streaming supported	128 Kbps	768 Kbps	ISDN, Ethernet/LAN	** Quad BRI Module ** MP Upgrade Kit  (Requires hardware exchange)	2	Quad BRI Module and software upgrade required for MP
<b>ViewStation H.323</b>	Medium or large room system 1-10 people	Document camera & VCR 2nd mic pod (optional) 2-port LAN hub * Streaming supported	Optional	768 Kbps	Ethernet/LAN	Quad BRI Module DCP Module V.35 Module MP Upgrade Kit	2	Quad BRI Module and software upgrade required for MP
		Optional Quad BRI Module	512 Kbps	768 Kbps	ISDN, Ethernet/LAN			
		Optional DCP Module	512 Kbps	768 Kbps	Lucent Definity ECS Ethernet/LAN			
		Optional V.35 Module	768 Kbps	768 Kbps	V.35/RS-449 Ethernet/LAN T1/E1, ATM, VPN			
<b>ViewStation MP</b>	Medium or large room system 1-10 people	On-demand multipoint capability Document camera & VCR 2nd mic pod (optional) * Streaming supported	512 Kbps	768 Kbps	ISDN, Ethernet/LAN	N/A	2	4 @ 128 Kbps 3 @ 256 Kbps ISDN
<b>ViewStation FX</b>	Boardroom, classroom or custom room system 1-30+ people	TV-quality video Supports 2nd PTZ camera RS 232 dataport SXGA resolution graphics support Built-in multipoint up to 4 @ 384 Built-in streaming capabilities International POTS add-in Dual microphones standard	Optional	2 Mbps	Ethernet/LAN	Quad BRI Module PRI Module V.35 Module	2+ (1 XGA)	4 @ 384 Kbps 3 @ 512 Kbps via ISDN or LAN
		Optional Quad BRI Module	512 Kbps	2 Mbps	ISDN, Ethernet/LAN			
		Optional PRI Module	1.472 T1 1.922 E1	2 Mbps	ISDN, Ethernet/LAN			
		Optional V.35 Module	1.472 T1 1.922 E1	2 Mbps	V.35/RS-449 T1/E1, ATM, VPN Ethernet/LAN			
<b>VS4000 Codec</b>	Custom room system 1-30+ people	TV-quality video Supports 2 external cameras RS 232 dataport SXGA resolution graphics support Built-in multipoint up to 4 @ 384 Built-in streaming capabilities On/off echo cancellor International POTS add-in Dual microphones standard	Optional	2 Mbps	Ethernet/LAN	Quad BRI Module PRI Module V.35 Module	2+ (1 XGA)	4 @ 384 Kbps 3 @ 512 Kbps via ISDN or LAN
		Optional Quad BRI Module	512 Kbps	2 Mbps	ISDN, Ethernet/LAN			
		Optional PRI Module	1.472 T1 1.922 E1	2 Mbps	ISDN, Ethernet/LAN			
		Optional V.35 Module	1.472 T1 1.922 E1	2 Mbps	V.35/RS-449 T1/E1, ATM, VPN Ethernet/LAN			

\*with optional Polycom StreamStation

\*\*Not Available in Asia or ROW

